

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

Listing of claims:

1. (Currently amended) A computer-readable medium having computer-executable instructions comprising:

assigning a value to a unique identifier that is used to identify a version of software associated with an executable, wherein the value is associated with update information that is used to update the corresponding version of the software;

generating a request to obtain location information of the update information using the unique identifier;

querying a first server for the location information using the request, wherein:

the location information includes information about a location of a second server that comprises the update information, and

the location information identifies the second server type;

linking the first server to the second server;

querying the second server for the update information using a protocol associated with the second server type identified in the location information;

receiving the update information from the second server; and

updating the version of the software identified by the unique identifier based on the update information.

2. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises providing a path to a look up HyperText Transfer Protocol (HTTP) symbol location server.

3. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises querying a Dynamic Host Configuration Protocol (DHCP) server and requesting Uniform Resource Identifiers (URIs) to query the second server for the update information.

App. No. 09/670,073

Amendment Dated April 8, 2005

Reply to Office Action of January 31, 2005

4. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises querying a Domain Name System (DNS) server for a service (SRV) record identifying the second server to be queried.

5. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises querying a directory service for the location information.

6. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises querying an Application Configuration Access Protocol (ACAP) server for the location information.

7. (Previously presented) The computer-readable medium of claim 1, wherein querying a first server further comprises querying a Lightweight Directory Access Protocol (LDAP) server for the location information.

8. (Currently amended) A computer-readable medium having computer-executable instructions comprising:

assigning a value to a unique identifier that is used to identify a version of a local file, wherein the value is associated with a symbol that is used to update the corresponding version of the local file;

creating a path to a symbol location server based on the unique identifier, wherein the unique identifier identifies a protocol associated with the symbol location server;

querying the symbol location server through the path for the symbol using the protocol;

receiving the symbol from the symbol location server through the path; and
updating software associated with the local file using the symbol.

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

9. (Previously presented) The computer-readable medium of claim 8, wherein assigning a value further comprises extracting the unique identifier from an image header of the local file.

10. (Previously presented) The computer-readable medium of claim 9, wherein a value is not replicated between differing versions of the local file.

11. (Previously presented) The computer-readable medium of claim 8, wherein receiving the symbol further comprises receiving a file comprising the symbol, wherein the file is stored in a local system memory.

12. (Previously presented) The computer-readable medium of claim 8, wherein querying the symbol location server further comprises querying the symbol location server with a user customized query which extracts over a back end store.

13. (Currently amended) A computer-readable medium having computer-executable instructions comprising:

assigning a value to a unique identifier that is used to identify a version of software associated with an executable, wherein the value is associated with update information that is used to update the corresponding version of the software;

generating a request using the unique identifier to obtain from a first server location information associated with a second server, wherein:

the second server comprises the update information, and

the location information identifies the second server type;

creating a path to the second ~~first~~ server;

querying the second ~~first~~ server through the path for the location information using the request using a protocol associated with the second server type identified in the location information;

receiving the update information from the second ~~first~~ server through the path;
and

App. No. 09/670,073

Amendment Dated April 8, 2005

Reply to Office Action of January 31, 2005

updating the version of the software identified by the unique identifier based on the update information.

14. (Previously presented) The computer-readable medium of claim 13, wherein receiving the update information further comprises receiving a reference location associated with the second server to access a file associated with the executable on the second server.

15. (Currently amended) The computer-readable medium of claim 13, wherein querying the second ~~first~~ server further comprises querying a server selected from a group consisting of a DHCP server, a DNS server, an ACAP server, and a LDAP server.

16. (Currently amended) The computer-readable medium of claim 15, wherein querying the second ~~first~~ server further comprises querying a set of servers in parallel.

17. (Currently amended) The computer-readable medium of claim 15, wherein querying the second ~~first~~ server further comprises querying a set of servers in a serial order.

18. (Currently amended) The computer-readable medium of claim 13, wherein querying the second ~~first~~ server further comprises packaging information extracted from the executable into a ~~HyperText Transfer Protocol (HTTP)~~ request and sending the HTTP request to the second ~~first~~ server.

19. (Currently amended) A computer-readable medium having computer-executable instructions comprising:

assigning a value to a unique identifier that is used to identify a version of software associated with an executable, wherein the value is associated with update information that is used to update the corresponding version of the software;

generating a request to obtain location information of the update information using the unique identifier;

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

querying a first server for the location information using the request, wherein:
the location information includes information about a location of a second
server that comprises the update information, and
the location information identifies the second server type;
receiving the location information from the first server;
creating a path to the second server based on the type of the update information;
querying the second server through the path for the update information using a
protocol associated with the second server type identified in the location information syntax
~~based on the location information;~~ and
updating the version of the software identified by the unique identifier based on
the update information.

20. (Previously presented) The computer-readable medium of claim 19,
wherein querying a first server further comprises querying the first server using metadata
associated with the executable.

21. (Previously presented) The computer-readable medium of claim 19,
wherein querying the second server further comprises querying the second server using metadata
associated with the executable.

22. (Previously presented) The computer-readable medium of claim 21,
wherein the metadata comprises metadata for debug files.

23. (Previously presented) The computer-readable medium of claim 21,
wherein the metadata comprises metadata for source files.

24. (Previously presented) The computer-readable medium of claim 19,
wherein querying the second server further comprises querying the second server for symbols
associated with the executable.

App. No. 09/670,073

Amendment Dated April 8, 2005

Reply to Office Action of January 31, 2005

25. (Previously presented) The computer-readable medium of claim 19, wherein querying the second server further comprises querying the second server for regression analysis data associated with the executable.

26. (Previously presented) The computer-readable medium of claim 19, wherein querying the second server further comprises querying the second server for performance analysis data associated with the executable.

27. (Previously presented) The computer-readable medium of claim 19, wherein querying the second server further comprises querying the second server for source code associated with the executable.

28. (Previously presented) The computer-readable medium of claim 19, wherein querying the second server further comprises receiving files comprising the update information.

29. (Currently amended) A computer-readable medium having computer-executable instructions for updating a software program associated with an executable file, comprising:

assigning a value to a unique identifier that is used to identify a version of software associated with the executable file, wherein the value is associated with update information that is used to update the corresponding version of the software;

packaging metadata extracted from the executable file into a ~~an~~ HTTP request, wherein the metadata is associated with the unique identifier;

creating a path to a locator server, wherein:

the locator server comprises location information for a server on which the update information is located, and

the location information identifies the server type;

sending through the path the HTTP request to the ~~locator~~ server, wherein the request corresponds to a protocol associated with the server type identified in the location information;

App. No. 09/670,073

Amendment Dated April 8, 2005

Reply to Office Action of January 31, 2005

receiving the update information from the ~~locator~~ server through the path; and
updating the version of the software identified by the unique identifier based on
the update information.

30. (Previously presented) The computer-readable medium of claim 29,
wherein packaging metadata further comprises packaging metadata to locate an updated version
of the executable file.

31. (Previously presented) The computer-readable medium of claim 29,
wherein packaging metadata further comprises packaging metadata for locating a debug file
associated with the executable file.

32. (Previously presented) The computer-readable medium of claim 29,
wherein packaging metadata further comprises packaging metadata to locate a specific build
version of the executable file.

33. (Previously presented) The computer-readable medium of claim 29,
wherein receiving the update information further comprises receiving an HTTP redirect.

34. (Previously presented) The computer-readable medium of claim 29,
wherein receiving the update information further comprises receiving a location of the server on
which the update information is located, and querying the server with the unique identifier for
the update information.

35. (Previously presented) The computer-readable medium of claim 34,
wherein querying the server further comprises providing a qualifier.

36. (Currently amended) A computerized system comprising:
a first server comprising location information for update information that is used
to update a corresponding version of software associated with a local file, wherein the version of

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

the software is identified by a unique identifier that has an assigned value associated with the update information, and further wherein the location information identifies the type of server that comprises the update information;

a second server comprising the update information, wherein:

the first server is linked to the second server through a path that is created based on the value, ~~and further wherein~~

the first server queries the second server through the path for the update information using a protocol associated with the second server type identified in the location information, and

the first server receives the update information from the second server through the path; and

a computer comprising the local file, wherein the first server provides the update information to the computer such that the version of the software identified by the unique identifier is updated based on the update information.

37. (Previously presented) The system of claim 36, wherein the update information comprises debug information.

38. (Previously presented) The system of claim 36, wherein the update information comprises solution access information.

39. (Previously presented) The system of claim 36, wherein the computer reads the update information from the second server.

40. (Previously presented) The system of claim 36, wherein the first server comprises a HyperText Transfer Protocol (HTTP) server.

41. (Previously presented) The system of claim 40, wherein the HTTP server comprises a Dynamic Host Configuration Protocol (DHCP) server having Uniform Resource Identifiers (URIs) for querying the second server.

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

42. (Previously presented) The system of claim 40, wherein the HTTP server comprises a Domain Name System (DNS) server having a service (SRV) record for identifying the second server.

43. (Previously presented) The system of claim 40, wherein the HTTP server comprises a directory service for providing the location information for the update information to the computer.

44. (Previously presented) The system of claim 36, wherein the first server comprises an Application Configuration Access Protocol (ACAP) server.

45. (Previously presented) The system of claim 36, wherein the first server comprises a Lightweight Directory Access Protocol (LDAP) server.

46. (Previously presented) The system of claim 36, wherein the computer is networked to the first and the second servers over the Internet.

47. (Currently amended) A computerized system comprising:
a first server comprising location information for update information that is used to update a corresponding version of software associated with an executable file, wherein the version of the software is identified by a unique identifier that has an assigned value associated with the update information, and further wherein the location information identifies the type of server that comprises the update information;
a second server comprising the update information, wherein the first server is linked to the second server through a path that is created based on the value; and
a computer comprising the executable file, wherein the first server is adapted to provide the computer with the location information, and further wherein the computer uses the location information to query the second server through the path for the update information using a protocol associated with the second server type identified in the location information such that

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

the version of the software identified by the unique identifier is updated based on the update information.

48. (Previously presented) The system of claim 47, wherein the first server is selected from a group consisting of a DHCP server, a DNS server, an ACAP server, and a LDAP server.

49. (Previously presented) The system of claim 47, wherein the computer is configured to query a hierarchy of first servers in serial order.

50. (Previously presented) The system of claim 47, wherein the computer is configured to query a hierarchy of first servers in parallel.

51. (Previously presented) The system of claim 47, wherein the update information comprises solution access information.

52. (Previously presented) The system of claim 47, wherein the computer is configured to query the second server, in an HTTP request format, for the update information using a qualifier associated with the executable file.

53. (Previously presented) The system of Claim 47, wherein the query to the second server is performed using metadata extracted from the executable file.

54. (Previously presented) The system of claim 53, wherein the metadata extracted from the executable file comprises metadata for a debug file associated with the executable file.

55. (Previously presented) The system of claim 53, wherein the metadata extracted from the executable file comprises metadata associated with regression analysis data for the executable file.

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

56. (Currently amended) A computer-readable medium having computer executable instructions to cause a computing system to perform a method for updating software associated with an executable file, comprising:

assigning a value to a unique identifier that is used to identify a version of software associated with an executable file, wherein the value is associated with update information that is used to update the corresponding version of the software;

creating a path from a lookup server to a server having the update information based on the value;

using the lookup server to identify location information for the server having the update information based on metadata extracted from the executable file, wherein:

the metadata is associated with the unique identifier, and

the location information identifies the server type;

packaging a an-HTTP query for retrieving the update information through the path, wherein the query corresponds to a protocol associated with the server type identified in the location information;

retrieving the update information; and

updating the version of the software identified by the unique identifier based on the update information.

57. (Previously presented) The computer-readable medium of claim 56, wherein using the lookup server further comprises providing a response to a requesting client from the lookup server.

58. (Previously presented) The computer-readable medium of claim 57, further comprising forwarding the location information to a requesting client as an HTTP redirect.

59. (Currently amended) A method for updating software associated with a local file, comprising:

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

assigning a value to a unique identifier that is used to identify a version of software associated with the local file, wherein the value is associated with update information that is used to update the corresponding version of the software;

packaging metadata extracted from the local file into ~~a an-HTTP~~ request to obtain the update information, wherein the metadata is associated with the unique identifier;

sending the HTTP request to a locator server;

receiving location information from the locator server, wherein the location information identifies the type of server that comprises the update information;

packaging ~~a an-HTTP~~ query for retrieving the update information based on the location information, wherein the query corresponds to a protocol associated with the type of server identified in the location information; and

updating the version of the software identified by the unique identifier based on the update information.

60. (Currently amended) The method of claim 59, wherein packaging the HTTP query further comprises qualifying the HTTP query to select a specific file version from the update information.

61. (Currently amended) The method of claim 60, wherein qualifying the HTTP query further comprises qualifying the HTTP query to select an updated file version associated with the local file.

62. (Currently amended) The method of claim 60, wherein qualifying the HTTP query further comprises qualifying the HTTP query to select a specific debug file associated with the local file.

63. (Currently amended) A server architecture comprising;
a first server comprising location information for update information that is used to update a corresponding version of software associated with an executable file, wherein the version of the software is identified by a unique identifier that has an assigned value associated

App. No. 09/670,073
Amendment Dated April 8, 2005
Reply to Office Action of January 31, 2005

with the update information, and further wherein the location information identifies the type of server that comprises the update information;

a second server linked to the first server based on the value, wherein the second server comprises the update information associated with the executable file;

means for interpreting metadata associated with the unique identifier received by the first server from a remote client;

means for generating a query for retrieving the update information using a protocol associated with the second server type identified in the location information;

means for redirecting the remote client to the second server, wherein the second server is adapted to interpret the a query from the remote client ~~for retrieving the update information;~~ and

means for updating the version of the software identified by the unique identifier based on the update information.